

ILLINOIS STATE GEOLOGICAL SURVEY

Page 1

Water Well	Top	Bottom
clay	0	17
sandy clay	17	20
dirty red sand	20	27
gray sand	27	35
gray clay	35	45
hard clay	45	49
coarse gray sand & gravel	49	52
fine sand	52	53
fine to coarse sand w/ gravel	53	54
fine gravel	54	55
coarse gravel w/ fine sand	55	59
shale	59	62

Total Depth

63

Casing: 20" from 0' to 50'

8" from -2' to 53'

Screen: 8' of 8" diameter 0.06 slot

Water from sand & gravel at 54' to 62'

Static level 22' below casing top which is 2' above GL

Pumping level 33' when pumping at 80 gpm for 3 hr(s)

Permanent pump installed at ' on , with a capacity of gpm

Driller's Log filed.

Sample set # 60872 49' - 59'

Received: 6/6/1977

Location source: Location from permit

Permit Date: May 19, 1977

Permit #: 60875

COMPANY Calhoun Drlg. Co.

FARM Albers Village of

DATE DRILLED March 21, 1978

NO. 5

ELEVATION 425' GL

COUNTY NO. 24774

LOCATION 40'S line, 312'W line of

LATITUDE 38.539490

LONGITUDE -89.611195

COUNTY Clinton

API# 1202724774 00

12-1N-5W