

ILLINOIS STATE GEOLOGICAL SURVEY

Page 1

Water Well	Top	Bottom
yellow soft sand	0	54
gray firm clay	54	66
gray firm sand gravel	66	100

Total Depth **100**

Casing: 5" PVC SDR 21 from -1' to 80'

4.5" PVC SCH 40 from 75' to 95'

4.5" PVC SCREEN from 95' to 100'

Screen: 5' of 4.5" diameter 0.02 slot

Grout: BENSEAL from 0 to 80

Water from sand gravel at 95' to 100'

Static level 17' below casing top which is 1' above GL

Pumping level 80' when pumping at 30 gpm for 1 hr(s)

Permanent pump installed at ' on , with a capacity of gpm

Remarks: Driller's Estimated Well Yield 30 gpm

Owner Address: 430 Feather Rd. Leland, IL

Address of well: 20476 Mill Rd. Prophetstown, IL 61277 Prophetstown
IL

Location source: Global Positioning System verified

Permit Date: January 9, 2018

Permit #: 195-005-18

COMPANY Geltz, N. H.

FARM McCullough, Brad

DATE DRILLED April 5, 2018

NO.

ELEVATION '

COUNTY NO. 24681

LOCATION

LATITUDE 41.657135

LONGITUDE -89.853569

COUNTY Whiteside

API# 1219524681 00

6-19N-6E