

ILLINOIS STATE GEOLOGICAL SURVEY

Page 1

Water Well	Top	Bottom
clay & stones	0	50
sandy clay & gravel	50	70
clay	70	75
broken limestone	75	80
limestone, seams @170', 12" thick 190'	80	205

Total Depth **205**

Casing: 6" STEEL from -1' to 85'

Grout: NAT CLAY SLURRY from 0 to 0

Water from limestone at 84' to 205'

Static level 70' below casing top which is 1' above GL

Pumping level 85' when pumping at 25 gpm for 2 hr(s)

Permanent pump installed at 105' on 12/29/1999, with a capacity of 19 gpm

Remarks: driller's estimated well yield 25 gpm

Owner Address: 2222 E. State St. Rockford, IL

Address of well: Shane's Way

Add'l loc info: Lot: 11 Subdivision: Eagle Point Est.

Location source: Aerial Photograph verified

Verified by: VJA on 8/31/2021

Permit Date: November 15, 1999 **Permit #:** 2608

COMPANY Rosenquist, Gerald Wilbur

FARM Miller Construction, John

DATE DRILLED December 2, 1999 **NO.**

ELEVATION 0' **COUNTY NO.** 31711

LOCATION

LATITUDE 42.423190 **LONGITUDE** -88.958543

COUNTY Winnebago **API#** 1220131711 00 **36-46N-2E**