

ILLINOIS STATE GEOLOGICAL SURVEY

Page 1

Water Well	Top	Bottom
yellow clay	0	8
brown clay	8	15
gray clay	15	31
gravel	31	35
gray clay	35	53
gravel with clay showing	53	55
gray clay	55	65
gravel	65	67
gray clay	67	92
green clay with gravel streaks	92	98
gray clay	98	126
gravel	126	146
gray clay	146	150

Total Depth **150**

Casing: 5" SDR 21 from -2' to 138'

5" STAINLESS STL SCREEN from 138' to 142'

Screen: 4' of 5" diameter 20 slot

Grout: EZ SEAL from 0 to 128

MUSCATINE from 128 to 142

Water from gravel at 126' to 146'

Static level 75' below casing top which is 2' above GL

Pumping level 80' when pumping at 24 gpm for hr(s)

Permanent pump installed at ' on , with a capacity of gpm

Remarks: Driller's Estimated Well Yield 24 gpm

Owner Address: 106 N Howard St. Roanoke, IL

Address of well: County Rd. 550 N Secor, IL Secor IL

Location source: Location from permit

Permit Date: June 6, 2006

Permit #: 203-1280-06

COMPANY James Layten

FARM Luginbuhl, Leslie

DATE DRILLED June 21, 2006

NO. 1

ELEVATION '

COUNTY NO. 22809

LOCATION

LATITUDE 40.667722

LONGITUDE -89.142417

COUNTY Woodford

API# 1220322809 00

31-26N-1E

ILLINOIS STATE GEOLOGICAL SURVEY

Page 2

Permit Date: June 6, 2006

Permit #: 203-1280-06

COMPANY James Layten

FARM Luginbuhl, Leslie

DATE DRILLED June 21, 2006

NO. 1

ELEVATION '

COUNTY NO. 22809

LOCATION

LATITUDE 40.667722

LONGITUDE -89.142417

COUNTY Woodford

API# 1220322809 00

31-26N-1E