

ILLINOIS STATE GEOLOGICAL SURVEY

Page 1

Water Well	Top	Bottom
fill and loam	0	4
clay yellow	4	15
clay gray	15	17
soil brown	17	26
clay gray	26	95
sand & gravel	95	103
sand fine-med	103	108
sand & gravel	108	122
sand fine medium	122	126

Total Depth **126**

Casing: 5" PVC SDR 21 from -2' to 118'

4.75" SCREEN from 118' to 122'

Screen: 4' of 4.75" diameter 30 slot

Grout: BENSEAL T-100 from 0 to 95

RED FLINT WELL PACK from 114 to 122

UNIMIN WELL PACK from 95 to 114

Water from sand & gravel at 95' to 122'

Static level 53' below casing top which is 2' above GL

Pumping level 57' when pumping at 30 gpm for 1 hr(s)

Permanent pump installed at 100' on 11/4/2016, with a capacity of 25 gpm

Remarks: Driller's Estimated Well Yield 30 gpm

Address of well: 2163 CR 1050 Secor, IL 61771 Secor IL

Location source: Global Positioning System verified

Permit Date: October 26, 2016

Permit #: 203-1813-16

COMPANY Sauder Well Drilling

FARM Gerber, Cory

DATE DRILLED November 1, 2016

NO. 1

ELEVATION '

COUNTY NO. 23362

LOCATION

LATITUDE 40.742361

LONGITUDE -89.126361

COUNTY Woodford

API# 1220323362 00

5-26N-1W